

DCN-DV-xx Delegate Unit with Voting

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Low susceptibility to mobile phone interference
- ▶ Compact, attractive and ergonomic design
- ▶ Five voting buttons
- ▶ Built-in loudspeaker and pluggable microphone
- ▶ Usable as a delegate unit or as a chairman unit

This Delegate Unit with Voting enables participants to speak, register a request-to-speak, listen to the speaker and vote. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has five voting buttons for all types of voting. The yellow indicator rings around the voting buttons are used to prompt users to register their presence, to start voting and to confirm their votes. When the unit's attendance LED is yellow, it indicates the delegate is present.

Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when the microphone is on)
- The unit accommodates two headphone connections, so the speaker can be heard clearly even in situations with excessive background noise
- The built-in loudspeaker is muted when the microphone is on to prevent acoustic feedback
- The unit can be used as a delegate unit, as a chairman unit (DCN-DBCM chairman buttons to be ordered separately) or as a delegate unit with auxiliary button. The auxiliary button is a versatile function, which can be used as an usher call for example

- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)
- The unit is available in a dark colored base

Controls and Indicators

- Five voting buttons with indicator rings around the buttons
- Unit activity/delegate presence indicator
- Microphone button with a red, green or yellow illuminated LED. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphone volume control buttons
- Recessed 'De-init' switch

Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) stereo jack type headphone sockets
- 2 m (78.7 in) cable terminated within a molded six-pole circular connector
- Six-pole circular connector for loop-through connections

Technical specifications

Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 Ohm < 1k Ohm
Output power	2 x 15 mW/32 Ohm

Mechanical

Mounting	Tabletop (portable or fixed mounting)
Dimensions (H x W x D)	(without microphone)
Tabletop	60 x 210 x 140 mm (2.36 x 8.27 x 5.51 in)
Weight	1.15 kg (2.54 lb)
Color top	Black (RAL 9017)
Color rear	Silver (RAL 9006)

Ordering information

DCN-DV-CN Delegate Unit with Voting (CN)

With voting (Chinese version).

Order number **DCN-DV-CN**

DCN-DV Delegate Unit with Voting

With voting.

Order number **DCN-DV**

Accessories

DCN-MICS Pluggable Short Microphone

length 310 mm (12.2 inch), silver

Order number **DCN-MICS**

DCN-MICS-D Pluggable Short Microphone Dark

length 310 mm (12.2 inch), dark

Order number **DCN-MICS-D**

DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch), silver

Order number **DCN-MICL**

DCN-MICL-D Pluggable Long Microphone Dark

length 480 mm (18.9 inch), dark

Order number **DCN-MICL-D**

DCN-DBCM Buttons Chairman (10 sets)

10 Sets

Order number **DCN-DBCM**

DCN-DISCLM Cable Clamp (25 pcs)

25 pieces

Order number **DCN-DISCLM**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com