

# DCN-DCS-xx Delegate Unit with Channel Selector

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Low susceptibility to mobile phone interference
- ▶ Compact, attractive and ergonomic design
- ▶ Channel selector with number and abbreviated channel name
- ▶ Built-in loudspeaker and pluggable microphone
- ▶ Usable as delegate or chairman unit

The Delegate Unit with Channel Selector enables participants to speak, register a request-to-speak and listen to the speaker. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has a built-in channel selector that makes it suitable for discussions in which more than one language is used and simultaneous interpretations are available. The channel selector includes two up and down channel select keys and a display showing the number and the abbreviation of the languages, enabling rapid selection of the required language channel.

## Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when microphone is on)
- Socket for pluggable microphones (DCN-MICS or DCN-MICL)
- The built-in loudspeaker speaker is muted when the microphone is on to prevent acoustic feedback.
- The unit can be used as a delegate unit or as a chairman unit (DCN-DBCM chairman buttons, to be ordered separately)

- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)

## Controls and Indicators

- Alphanumeric display for language channel selection with number and abbreviated channel name
- Microphone button with a red, green or yellow illuminated LED. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphones have volume control buttons
- Recessed 'De-init' switch

## Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) stereo jack type headphones sockets
- 2 m (78.7 in) cable terminated with in a molded six-pole circular connector.
- Six-pole circular connector for loop-through connections

## Technical specifications

### Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 Ohm < 1k Ohm
Output power	2 x 15 mW/32 Ohm

### Mechanical

Mounting	Tabletop (portable or fixed mounting)
Dimensions (H x W x D)	<b>(without microphone)</b>
Tabletop	60 x 210 x 140 mm (2.36 x 8.27 x 5.51 in)
Weight	1.15 kg (2.54 lb)
Color top	Black (RAL 9017)
Color rear	Silver (RAL 9006)

## Ordering information

### DCN-DCS-CN Delegate Unit with Channel Selector (CN)

With channel selector (Chinese version).

Order number **DCN-DCS-CN**

### DCN-DCS Delegate Unit with Channel Selector

With channel selector.

Order number **DCN-DCS**

### Accessories

#### DCN-MICS Pluggable Short Microphone

length 310 mm (12.2 inch), silver

Order number **DCN-MICS**

#### DCN-MICS-D Pluggable Short Microphone Dark

length 310 mm (12.2 inch), dark

Order number **DCN-MICS-D**

#### DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch), silver

Order number **DCN-MICL**

#### DCN-MICL-D Pluggable Long Microphone Dark

length 480 mm (18.9 inch), dark

Order number **DCN-MICL-D**

### DCN-DBCM Buttons Chairman (10 sets)

10 Sets

Order number **DCN-DBCM**

### DCN-DISCLM Cable Clamp (25 pcs)

25 pieces

Order number **DCN-DISCLM**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
12000 Portland Avenue South  
Burnsville MN 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
audiosupport@us.bosch.com  
www.boschsecurity.com

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
al.securitysystems@bosch.com  
www.boschsecurity.com