



Features

- * 1/4" SONY SUPER HAD CCD.
- * 18 times optical zoom, $f=4.1\text{mm}(\text{wide})\text{-}73.8\text{mm}(\text{tele})$, $F=1.4\text{-}F3.0$.
- * 960TVL.
- * High strength double glazed aluminium lunerite bottom canopy, high temperature resistance and resistant to corrosion.
- * 360° continuous rotation, the max speed $300^\circ/\text{s}$.
- * 4 roads alarm input and one road alarm output.
- * 6 roads programmable tour check, 128 pre-points, with self-learning function.
- * OSD display English menu, pre-point title and camera address, etc. Displayable.
- * Integrated multi protocols, baud rate optional, multi-cameras self-adaptation and standard RS-485 control.
- * Packed ports, with hot plug function, convenient for aloft working.
- * Zone hidden selection function (max 8 programmable hidden zones).
- * Built in 3KV lightning protection, surge protection and instant over voltage protection.
- * Adopt all-weather shield, built in automatic thermostatic apparatus.
- * Adopt AC24V power and line lock available.
- * About forty four hundred thousand pixel, 12 times digital zoom.
- * Lowest illumination: 1.0LX (standard) (F1.4,50IRE).

Specifications

Model	TS-0692
Upper canopy material	Aluminium alloy
Wire balloon material	Imported acrylic optical material
Horizontal Turning	$0^\circ \sim 300^\circ/\text{s}$
Vertical Rotation	$0^\circ \sim 120^\circ/\text{s}$
Level Angle	360° Infinite place
Vertically Angle	90°
Pre-points	128 Pieces (max)
Control method multi protocol	RS485
Power	AC24V
Power Consumption	35VA
Relative Humidity	90%
Dimensions	219x262mm
Weight	4kg