



Features

- Latest digital design.
- With microphone, speaking button and indicator lamp that can show and control the state of speech.
- Single projection; With Anti-gas sonic boom and wind shield
- With president priority key; the system sound can be prompted to attract attendances' attention; can be set to terminate for permanent or suspend microphone status of all the speakers.
- The chairman unit can be placed in any position in loop.
- The chairman unit is unrestricted by the limiting function.
- With under-wound capacitive microphone pole and speak halo instructions.
- High sensitivity microphone.
- The power for the delegate units is supplied by the master controller at 24 safe voltage.
- T-shaped 8-core line for unit connection.
- Two groups of 3.5mm stereo sound output socket; can be used as record and earphone connection.
- Built-in hi-fi speaker; volume control (the speak automatically mute when the microphone be turned on).
- With voting,electing,discussing functions.
- With automatic video-tracking function.
- With a microphone unit connecting cable.
- In accordance with Enternational Electrical Equipment Certification standards (IEC 60914) and the International Safety Standard UL or CE certification.

Discussion Video Voting Delegate Unit TH-0802A



Features

- Latest digital design.
- With microphone, speaking button and indicator lamp that can show and control the state of speech.
- Single projection; With Anti-gas sonic boom and wind shield.
- With under-wound capacitive microphone pole and speak halo instructions.
- High sensitivity microphone.
- The system power supply for all the delegate unites is provided by the main frame at 24 safe voltage.
- T-shaped 8-core line for unit connection.
- Two groups of 3.5mm stereo sound output socket; can be used as record and earphone connection.
- Built-in hi-fi speaker; volume control (the speak automatically mute when the microphone be turned on).
- With voting,electing,discussing functions.
- With automatic video-tracking function.
- With a microphone unit connecting cable.
- In accordance with Enternational Electrical Equipment Certification standards (IEC 60914) and the International Safety Standard UL or CE certification.

Specifications

Model	TH-0802/TH-0802A
Frequency Response	100-13KHz
Sensitivity	-44dB ± 2dB
Reference sound-receiving distance	20-120cm
Tube length	420mm
Dimension of the appearance	205 × 150 × 55mm
Net Weight	0.9Kg
Others	32 e-volume digital adjusting display