

## TH-0802M

### Conference System Controller



#### Features

The high performance compressive master controller is designed especially for conference discussion and voting. It meets all the requirements of modern conference that can manage discussion, decision, voting and commenting according system. It is highly integrated and easy to install.

- The master controller operates by connecting to the computer; Can connect 64 delegates airman units; with master extension the communication capacity reaches 250 sets.
- Achieve functions of conference discussion, multi-voting, with camera tracking host to realize automatically camera tracking.
- Main unit sets microphone turn-on quantity and mode to control conference order.
- Voice transferred by built-in hi-fi speaker and external earphone jack.
- Audio input and output interfaces can connect sound reinforcement equipments and recording equipments. Built 2 × 50W power.

#### Specifications

Model	TH-0802M
Max Delegate Mic Qty	≤250 units
Frequency Response	20-20k Hz
S/N Ratio	>96dB
Crosstalk	>84dB
THD	<0.1 % @1kHz
Power Supply	AC 120V or 220V; 50-60Hz
Input	Balanced Mic input and unbalanced Aux input
Output	unbalanced line output, unbalanced REC output and balanced line output
Output Loading	>1K Ω
Control Port	RS232 port for PC and RJ45 port for Video Tracking Controller
Effector Connector	Effector input and output
Speaker Output	RMS 50 watts stereo output for 4-16 Ω speakers.
Power Consumption	400 watts

Communication Cable	Dedicated 8 pins cable
Dimension (W×H×D)	480 x 360 x 85mm
Weight	12.7kg