



Highly Integrated Digital Cover Delegate Unit TS-0614A



Features

- Delicate and elegant clamshell design.
 - Adopt hi-fi flat-panel loudspeakers for more evenly distribution.
 - Integrate the function of speech and voting.
 - Heart-shaped projection capacitive microphone with two types of indicator lights.
 - With earphone jacks; clear sound; with a knob to adjust the volume.
 - The president unit has the right to approve or reject the delegate's speech apply.
 - The president unit is unrestricted by the number of speakers.
 - The President unit has the priority to control conference order in full power.
- Chairman unit can be series-connected anywhere in the circuit.
- Power supplied by the master controller at 24V safe voltage.
 - With howl inhibition function; when the microphone is turned on, the built-in speaker will automatically turn off to prevent transfusion voice.
 - "Hand in hand" cable-series mode, easy to install and maintain.

Specifications

Model	TS-0614/TS-0614A
Power Supply	DC24V(supplied by controller)
Unit Interface	8 core air plugs
Power Consumption	3W
Headphone Output	9dBu, 8 – 32Ω, 3.5mm Micro-socket
Speaker Power	2W
Microphone Type	heart-shaped capacitive type
Projection Characteristic	heart-shaped
S/N	> 80dB
Crosstalk Attenuation	> 80dB
Distortion	< 0.1%
Frequency Response	60 – 16KHz
Sensitivity	- 22dBv/Pa
Dimensions	247L x 155W x 60H(mm)
Color	Black